

## **TECHNICAL SHEET**

### **FFP – Finixa flat foam pad - 115 x 115mm**

#### **Description**

Patent pending sanding system, based on open mesh fairy cloth and open pore flexible foam. Suitable for optimizing the surface by hand sanding with lowest scratch depth. It is used where conventional abrasives can be too aggressive or results in uneven finish.

#### **Technical**

Grit: Aluminum Oxide  
Coating: Patented Coating Process  
Bonding: Patented Coating Resin  
Grit Range: 320, 500, 800, 1500  
Available dimension: sheets 115x115mm

#### **Properties**

Possibility to work dry and wet.  
Open mesh patented structure. 3D abrasive coating  
Working temperature lower than standard products  
Very Long lifetime  
Optimized pressure equalization

#### **Advantages**

Dry sanding increase productivity: check immediately work results.  
Low clogging thanks to 3D structure, keep dust in the 3D structure  
Uniform pressure thanks to backing foam  
No finger prints on the surface  
Adaptable on shaped surfaces.  
Tear Resistance and cut resistance on shaped edges.

#### **Application**

Manual sanding of round edges, convex or concave.  
Fine sanding on flat areas  
Fine sanding of primer, paint and lacquers  
Sanding for blanding  
Mat sanding

*The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.*